


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
05/05/17	F	DIM. 57.50 WAS 57.40 ADDED DIM. $\phi 3.10$	T.B.	B.S.	
05/12/17	F	DIM. 150.0 was 152.4	T.B.	B.S.	
03/06/19	G	UPDATED TO :ROHS COMPLIANT"	T.B.	B.S.	

NOTES:

1. MATERIAL:

HOUSING : POLYPROPYLENE  
 FLAMMABILITY RATING: UL94 HB, UL FILE NO. E216959  
 TEMPERATURE RANGE:  $-10^{\circ}\text{C}$  TO  $+100^{\circ}\text{C}$   
 RIVETS: BRASS, NICKEL PLATED.  
 SPRING: SPRING STEEL, NICKEL PLATED.  
 Wires: 26AWG, UL1007, CSA, TR64, 300V,  $80^{\circ}\text{C}$   
 CONTACT RESISTANCE: UNDER  $50\text{m}\ \Omega$  FOR  $\pm$  CONTACTS PER  
 EIA-540J000  
 ROHS COMPLIANT

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735			
decimal $\pm .5$ (.020)		Scale	Drawn By B.S.	
Fractional $\pm .8$ (.030)	Title THREE "AA" CELL HOLDER			
Angular $\pm 3^{\circ}$	Date 03/06/19	Drawing Number BC3AAW		
			Approved By T.B.	