


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
11/26/05	B	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
12/02/05	C	REMOVED "SOLDER DIPPED TAILS" FROM SPEC.	T.B.	B.S.	
6/13/14	D	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	



## SPECIFICATION

HOLDER: SELF-EXTINGUISHING THERMOPLASTIC POLYESTER PBT, BLACK, UL94V-0  
 CONTACTS: 301 - 304 SPRING TEMPER STAINLESS STEEL, NICKEL PLATED,

FLAMMABILITY RATING, 94V-0, FILE NO. E88499(M)


DIELECTRIC STRENGTH: 560V/ MIL AT 25°C FOR 5 SEC.

TEMPERATURE RANGE: -55°C TO +180°C

RESISTANCE TO SOLVENTS: Xylene; Ethyl acetate; Butyl, Methyl & propyl alcohol;  
 Refrigerants; Heptane; Toluene.

ROHS 2 COMPLIANT

## PCB LAYOUT

Tolerance (Except as noted)	 <b>Memory Protection Devices, Inc</b> 200 Broad Hollow Road, Farmingdale, New York 11735		
decimal $\pm .5$ (.020)		Scale 2=1	Drawn By T.S. Approved By T.B.
Fractional $\pm .8$ (.030)	Title BH-2N LITHIUM BATTERY HOLDER		
Angular $\pm 3^\circ$	Date 6/13/14	Drawing Number BH-2N	